



# Model PW666i

## Specifications

### Voltage generators

Setting range	
6-phase ac (L-N)	6×0~150V
1-phase ac (L-L)	1×0~300V
dc (L-N)	6×0~±150V
Power	
6-phase ac (L-N)	6×60VA at 150V
1-phase ac (L-N)	1×120 VA at 300V
	(two generators in series)
dc (L-N)	6×40 W at ±150 V
Accuracy	
	error < 0.08 % rd.+0.02 % rg. guar., at 0~150 V
	error < 0.04 % rd.+0.01 % rg. typ., at 0~150 V
Ranges	
	150V
Resolution	
	5mV for 150Vac
Distortion	
	< 0.05 % typ., (< 0.1 % guar.)

### Current generators

Setting range	
6-phase AC (L-N)	6×0~32A
3-phase AC (2L-N)	3×0~64A
1-phase AC (6L-N)	1×0~180A
dc (6L-N)	1×0~±90A
Power	
6-phase AC (L-N)	6×450VA typ. at 32A 6×400VA guar. at 32A
3-phase AC (2L-N)	3×800VA typ. at 64A 3×700VA guar. at 64A
1-phase AC (6L-N)	1×1200VA typ. at 180A 1×1000VA guar. at 180A
1-phase DC (6L-N)	1×1400W typ. at 90A 1×1000W guar. at 90A
Max compliance	
voltage (L-N) (L-L)	21Vpk/42Vpk
Accuracy	
	error < 0.15 % rd.+0.05 % rg. guar., at 0~32A
	error < 0.05 % rd.+0.02 % rg. typ., at 0~32A
Ranges	
	32A
Resolution	
	1mA
Distortion	
	< 0.05 % typ. (< 0.1 % guar.)
General	
Frequency	
Sine signal	DC, 1~2000Hz
Transient signal	dc~10.0 kHz
Accuracy	
	±1ppm
Resolution	
	0.001 Hz

### Phase

Angle range	-360°~+360°
Accuracy	<0.05° typ., <0.1° guar. at 50/60Hz
Resolution	±0.001°

### Auxiliary dc supply

Voltage range	0~300V
Power	88W at 110V, 176W at 220V, 120W at 300V
Accuracy	error < 0.1 % rg. typ. (< 0.5 % rg. guar.)

### Power supply

Nominal input voltage	110~240Vac
Permissible tolerance	90~260Vac
Nominal frequency	50/60Hz
Permissible frequency	45~65Hz

### Binary inputs Group1

Number	8
Input characteristics	0~400Vdc threshold or potential free
Sample rate	20kHz
Time resolution	50μs
Max. measuring time	infinite
Debounce/Deglitch time	0~25ms
Counting function	< 3kHz at pulse width>150μs
Galvanic isolation	8 galvanically isolated

### Binary inputs Group2

Number	4
Input characteristics	0~+5Vdc or dry contact
Sample rate	100kHz
Time resolution	50μs
Max. measuring time	infinite
Debounce/Deglitch time	0~25ms
Max. counting frequency	100kHz
Pulse width	< 3μs
Threshold voltage	2V
Voltage hysteresis	0.8V
Max. input voltage	+5V

### Binary outputs, relay

Number	4
Type	Potential free relay contacts, software controlled
Break capacity ac	Vmax: 300Vac /Imax: 8A /Pmax: 2000VA
Break capacity dc	Vmax: 300Vdc /Imax: 8A /Pmax: 150W

### DC voltage measuring input

Measuring range	0~±10V
Accuracy	error < 0.02% rg. typ. (< 0.05% rg. guar.)
Input impedance	100KΩ

### DC current measuring input

Measuring range	0~±20mA
Accuracy	error < 0.02% rg. typ. (< 0.05% rg. guar.)
Input impedance	50Ω

### Low level outputs

Setting range	12×0~10Vpk
Max. output current	1mA
Accuracy	error < 0.025 % typ. (< 0.07 % guar.) at 1~10Vpk
Resolution	250μV
Distortion(THD+N)	< 0.05 % typ. (< 0.1 % guar.)
Connection	19 pin combination socket(rear side)

### In-built monitoring and recording

Monitoring	currents and voltage outputs
Recording	analog outputs, binary inputs/outputs status
Mode	real time monitoring, no external wiring is required
Recording length	16s

### External analog recording unit (optional)

Channel	: 10
See details of optional accessory AR-10	

### IEC61850 upgrade

Interpretation hardware is in-built. Please contact the supplier for options to activate the IEC61850 software support function

### Environmental conditions

Operation temperature	0~+50°C
Storage temperature	-25~+70°C
Relative humidity	5~95% non - condensing
EMC (Emission)	IEC-61000-3-2/3
EMC (Immunity)	IEC 61000-4-2/3/4/5/6/11
Safety	IEC 61010-1

### Others

PC connection	Ethernet, 10M/100M
External amplifier interface	Circular connector
Current booster interface	Circular connector
Synchronization control interface	Coaxial cable connector
GPS interface	RS232
Ground Socket (earth)	4 mm banana socket; front side
Weight	20kg
Dimensions (W x H x D)	360mm×157mm×427 mm



## PONOVO POWER CO., LTD.

2F,4Cell, Tower C, In.Do Mansion, No.48A Zhichun Road, Haidian District Beijing, PR China (100098)  
Tel. +86 (10) 8275 5151 (reception) Tel. +86 (10) 82755151 ext.8887 (direct)  
Fax. +86 (10) 82755151-8103 info@ponovo.com.cn www.ponovo.com.cn